

Diversitech's DD series of industrial downdraft tables are the trusted choice of North America's largest manufacturers, and are built to withstand the most demanding applications. Any fumes, smoke or dust from your production activities can be captured right as they are produced, before compromising your indoor air quality. Your choice of standard table sizes range from 3'x4' to 5'x10', and larger worksurfaces can be easily created by "mirroring" multiple tables.

All downdraft tables come fitted with multi-stage spark arrestance baffles, dual 10" diameter exhaust silencers and an automatic reverse-pulse filter cleaning system to help reduce maintenance requirements. Many options and accessories are available for the DD series of downdraft tables, and tables can be custom configured and built-to-order in almost any configuration.

Flexible, all-in-one, downdraft solution for dust, smoke, or fumes produced from welding, grinding, deburring, cutting, sanding, finishing, soldering, painting, or mixing.

Features:

- High capture face velocity (250fpm)
- Multi-stage spark arrestance baffling
- Industrial swivel-casters
- · Reverse pulse cleaning system

Benefits:


- Hands-free capture-at-source
- Low maintenance, automatic self-cleaning system included
- Complies with OSHA guidelines for safe capture of dust, smoke, and weld fumes











Welding, Grinding & Deburring Kit:

- Side and back walls
- Metal mesh pre-filter
- Grounding lug

Plasma Cutting Kit:

- 2" high steel bar grating
- Slag collection baffle with 3/4" gravel
- Metal mesh pre-filter



VOC & Paint Kit:

- Side and back walls
- Paint arrestor pre-filter
- Reversible carbon canister afterfilter



Clean Air Workstation:

- Side and back walls (48" high w/top cover)
- Dust & vapor proof light kit
- · Backdraft hood







Primary Filters

NANOTECH XV

MERV 15 efficient cartridge filter captures particles at the submicron level, and surface-loading technology allows dust to be easily dislodged during cleaning with compressed air.



EFFICIENCY:
FILTER MEDIA:
MEDIA AREA:
COATING:
END CAP:
CLEANING METHOD:
MAX TEMP:
FLANGE:

MERV 15 NANOFIBER 139 SQ.FT. FIRE RETARDANT OPEN/CLOSED COMPRESSED AIR 180° F / 82° C

After Filters

%HEPA

The HEPA cartridge filter captures particles at the submicron level, it provides the highest level of filtration efficiency 99.97% at 0.3 micron.



 EFFICIENCY:
 99.97% AT 0.3 MICRON FILTER MEDIA:
 HEPA

 MEDIA AREA:
 24" × 24" × 11½"

 COATING:
 NONE

 END CAP:
 N/A

 CLEANING METHOD:
 DISPOSABLE MAX TEMP:

 FLANGE:
 NONE

POLYTECH X

High strength, high efficiency (MERV 11) cartridge filter made from 100% spun-bond polyester that lowers costs, by allowing for water-based cleaning of captured contaminants.



EFFICIENCY:
FILTER MEDIA:
MEDIA AREA:
COATING:
END CAP:
CLEANING METHOD
MAX TEMP:
FLANGE:

MERV 11 SPUNBOND POLY 55 SQ.FT. WATER REPELLENT OPEN/CLOSED AIR + WATER WASH 180° F / 82° C YES

CARBOTECH 50

Reversible steel canister filled with 44 lbs of activated carbon to filter VOC fumes and odors. Double the filter life by flipping the canister top-to-bottom, allowing for adequate contaminant distribution through the media.



 WEIGHT:
 44 LBS

 FILTER MEDIA:
 CARBON

 MEDIA THICKNESS:
 2.8-6**

 COVER:
 3/4" ANTIBACTERIAL

 END CAP:
 TWIST LOCK REMOVABLE

 CLEANING METHOD:
 NONE

 MAX TEMP:
 1175° F / 80° C

 FLANGE:
 NONE


IMPORTANT: If your equipment was purchased after <u>November 15, 2018</u>, a Replacement Filter Card, featuring filter details and simple instructions to easily order replacement filters, will be located on the filter door.


Specifications


			P	ower		Nominal	Static	Face	Noise		
Model	Motor (H.P)	Phase (hz)	@230V F.L.A (amps)	@460V F.L.A (amps)	@575V F.L.A (amps)	Airflow (CFM)	Pressure (in.)	Velocity (FPM)	@5ft (dB)		
Industrial Downdraft Tables, three phase											
DD-3X4	5.0	3P/60Hz	15.2	7.6	6.1	4300	4.0	450	79		
DD-3X6	5.0	3P/60Hz	15.2	7.6	6.1	4300	4.0	325	79		
DD-0/(0	7.5	3P/60Hz	22.0	11.0	9.0	5050	4.0	375	81		
DD-3X8	7.5	3P/60Hz	22.0	11.0	9.0	5050	4.0	330	81		
	10.0	3P/60Hz	28.0	14.0	11.0	6300	4.0	338	83		
Industrial Multi-operator Downdraft Tables, three phase											
DD-4X4	5.0	3P/60Hz	15.2	7.6	6.1	4300	4.0	425	79		
DD-4X6	7.5	3P/60Hz	22.0	11.0	9.0	5050	4.0	325	81		
	10.0	3P/60Hz	28.0	14.0	11.0	6300	4.0	375	83		
DD-4X8	10.0	3P/60Hz	28.0	14.0	11.0	6300	4.0	300	83		
DD-5X10	15.0	3P/60Hz	42.0	21.0	17.0	8600	4.0	330	85		











Dimensions **

Difficitations											
	Exhaust	Footprint (in.)			Worksurface (in.)		Table Height	Net Weight	Exhaust		
	Diameter									Overhang	
Model	(in.)	Length	Width	Height	Length	Width		(lbs.)	[g]	[h]	
		[b]	[a]	[C]	[e]	[d]	[f/S&B/CAW]			(in.)	
Downdraft Tables, Stand	ard Size										
DD-3X4	10 x 2	43	62	68.5	42	48	36/69/84	258	14	6	
DD-3X6	10 x 2	43	87	68.5	42	72	36/69/84	329	14	6	
DD-3X8	10 x 2	43	111	68.5	42	96	36/69/84	421	14	6	
DD-4X4	10 x 2	49	63	68.5	48	48	36/69/84	621	14	6 x 2	
DD-4X6	10 x 2	49	87	68.5	48	72	36/69/84	729	14	6 x 2	
DD-4X8	10 x 2	49	111	68.5	48	96	36/69/84	875	14	6 x 2	
DD-5X10	10 x 2	61	155	68.5	60	120	36/69/84	1107	34	12 x 2	
Downdraft Tables, extended overhang											
DD-3X4-EO	10 x 2	49	63	68.5	48	48	36/69/84	258	14	12	
DD-3X6-EO	10 x 2	49	87	68.5	48	72	36/69/84	329	14	12	
DD-3X8-EO	10 x 2	49	111	68.5	48	96	36/69/84	421	14	12	
DD-4X4-EO	10 x 2	61	63	68.5	60	48	36/69/84	621	14	12 x 2	
DD-4X6-EO	10 x 2	61	87	68.5	60	72	36/69/84	729	14	12 x 2	

^{**} Product dimensions are based on base-models and may vary depending on selected product features. Please contact us for an accurate shipping quote.

HEAD OFFICE

1200 55th Avenue Montreal, QC H8T 3J8

DISTRIBUTION CENTERS

CANADA Montreal, QC Toronto, ON
UNITED STATES Trenton, NJ Chicago, IL Reno, NV





